



BILL OF MATERIAL	
DESCRIPTION	MATERIAL
'A' COVER & TUBE	NEOPRENE
'B' FEMALE UNION	COATED DUCTILE IRON
BODY REINFORCING	NYLON
STABILIZING RING	CARBON STEEL
CABLES	COATED CARBON STEEL

MAX. TEMPERATURE: 230° F

TAG #	LOC.	DIA[IN.]	KEFLEX PART #	DESIGN PRESS @170 F	OAL	AXIAL COMP.	AXIAL EXT.	LATERAL DEFL.	ANGULAR DEFL.
		3/4"	F006CNN080	150	8"	7/8"	1/4"	7/8"	32°
		1"	F010CNN080	150	8"	7/8"	1/4"	7/8"	25°
		1 1/4"	F012CNN080	150	8"	7/8"	1/4"	7/8"	20°
		1 1/2"	F014CNN080	150	8"	7/8"	1/4"	7/8"	17°
		2"	F020CNN080	150	8"	7/8"	1/4"	7/8"	13°
		2 1/2"	F024CNN080	150	8"	7/8"	1/4"	7/8"	10°
		3"	F030CNN080	150	8"	7/8"	1/4"	7/8"	8°

DRAWN	DJM	KEFLEX PRODUCTS 1425 LAKE AVENUE WOODSTOCK, ILLINOIS 60098			
DATE	30APRIL15				
CHECKED		TITLE			
APPROVED	DG	NEOPRENE TWIN SPHERE CONNECTOR WITH FEMALE THD. UNION			
QC		SIZE	FSCM NO.	DWG NO.	REV
FILE	SUBNTSC100.DWG	A	87738	SUBMITTAL DRAWING	A
JOB	EJ2	SCALE NONE		SHEET 1 OF 1	

SUBMITTED BY:	DATE
CLIENT APPROVAL	DATE